



DIMENSION TABLE

CATALOGUE NO.	Size	A	B	C	D	D1	D2	APPROX WT. (kgs)
112A 10	3/8"(FG)	67	13	89	53	22	31	0.530
112A 15	1/2"(FG)	67	13	89	53	22	31	0.580
112A15	1/2"(IC)	67	13	89	53	22	31	0.550
112A 20	3/4"(IC)	93	17	95	76	33	43	0.880
112A 25	1"(IC)	102	20	98	76	33	43	0.935
112A 35	1 1/2"(IC)	132	28	105	110	55	55	1.650
112A 50	2"(IC)	160	35	114	132	64	68	2.850

How to read the catalogue:

112A 15 BR/CF8 BN/V BSP/NPT MO

- Series 2-way Normally Closed, Pilot Operated
- Size of valve/ Port size.
- Body material (Brass / CF8)
- Seating material (Buna Nitrile/Viton)
- End Connection (BSP / NPT)
- Manual Override

Coil Voltage:

M36 SQ H-18/12 WP-65

- Size of Coil.
- Coil Type (Square)
- Class of Insulation. Coil VA (AC) or Watts (DC)
- Class of Electrical Protection.

110V 50Hz AC/DC

- Electrical Voltage, Std. 230, 110, 24 AC / 24 V DC
- Hertz
- Characteristics (AC / DC)

Office At.:
 PUNE
 NEW DELHI
 KOLKATA
 CHENNAI
 BANGALORE
 HYDERABAD
 BARODA

Contact No.:
 +91 (20) 2712 0776
 +91 (11) 2646 0811
 +91 (33) 2230 2471
 +91 (44) 40282503
 +91 (80) 42911261
 +91 (40) 30916849
 +91 (26) 52345078